

# 92

## AGE series

### 92X92X25mm

#### ● General Specification

- Motor / DC single phase brushless motor
- Material / Frame : PBT (94V-0) ; Impeller : PBT(94V-0)
- Operation temp. / Two ball bearing : -10°C~70°C  
FMB,sleeve Bearing : -10°C~50°C
- Storage temp. / -40°C~80°C
- Non-condensing environment
- Weight / 85g



#### ● Specification \*Bearing system B:two ball bearing F:fluid bearing S:sleeve bearing

Model	*Bearing System	Rated Voltage	Operating Voltage	Rated Current	Rated Speed	Maximum Air Flow		Maximum Static Pressure		Sound Level	P-Q Curve
						m <sup>3</sup> /min	CFM	Pa	In-H <sub>2</sub> O		
P/N	B / S / F	V	V	A	RPM					dBA	No.
AGE09225_12J	B / F / S	12	7.0~13.2	0.12	2100	1.05	37.0	23.4	0.09	25	①
AGE09225_12L	B / F / S	12	7.0~13.2	0.14	2450	1.22	43.0	31.4	0.13	30	②
AGE09225_12M	B / F / S	12	7.0~13.2	0.17	2850	1.35	47.5	41.6	0.17	34	③
AGE09225_12H	B / F / S	12	7.0~13.2	0.20	3200	1.61	56.8	57.5	0.23	38	④
AGE09225_12U	B / F / S	12	7.0~13.2	0.35	3800	1.81	64.0	64.4	0.26	45	⑤
AGE09225_12V	B / F / S	12	7.0~13.2	0.41	4200	2.16	76.1	87.5	0.35	49	⑥
AGE09225_24J	B / F / S	24	14.0~26.4	0.06	2100	1.05	37.0	23.4	0.09	25	①
AGE09225_24L	B / F / S	24	14.0~26.4	0.08	2450	1.22	43.0	31.4	0.13	30	②
AGE09225_24M	B / F / S	24	14.0~26.4	0.10	2850	1.35	47.5	41.6	0.17	34	③
AGE09225_24H	B / F / S	24	14.0~26.4	0.15	3200	1.61	56.8	57.5	0.23	38	④
AGE09225_24U	B / F / S	24	14.0~26.4	0.20	3800	1.81	64.0	64.4	0.26	45	⑤
AGE09225_24V	B / F / S	24	14.0~26.4	0.22	4200	2.16	76.1	87.5	0.35	49	⑥
AGE09225_48J	B / F / S	48	28.0~56.0	0.05	2100	1.05	37.0	23.4	0.09	25	①
AGE09225_48L	B / F / S	48	28.0~56.0	0.06	2450	1.22	43.0	31.4	0.13	30	②
AGE09225_48M	B / F / S	48	28.0~56.0	0.08	2850	1.35	47.5	41.6	0.17	34	③
AGE09225_48H	B / F / S	48	28.0~56.0	0.10	3200	1.61	56.8	57.5	0.23	38	④

#### ● Drawing & panel out-cuts

#### ● Characteristic Curves

