

80

AGF series

80X80X25mm



● General Specification / 一般規格

- Motor / DC brushless motor
- Material / Frame : plastic(94V-0)
Impeller : plastic(94V-0)
- Bearing / Ball bearing;FMB
- Weight / 85g
- 馬達 / 直流單向無刷馬達
- 材質 / 框：塑膠(94V-0)
葉：塑膠(94V-0)
- 軸承 / 滾珠軸承;FMB
- 重量 / 85克

● Specification / 詳細規格 * 軸承/bearing B: 雙滾珠/ball bearing F:FMB S: 含油軸承/sleeve bearing

Model	Bearing	Voltage	Operating Vol.	Current	Speed	Max. Air Flow	Max. Static Pressure	Sound	Weight		
機型	軸承	電壓	操作電壓	電流	轉速	最大風量	最大風壓	噪音	重量		
P/N	B/S/F	V	V	A	RPM	m ³ /min	CFM	mm-H ₂ O	In-H ₂ O	dBA	g
AGF08025*12L	B	12	6.0~13.2	0.46	7000	2.47	87.04	21.12	0.83	49.51	107
AGF08025*12M	B	12	6.0~13.2	0.60	7600	2.68	94.55	23.57	0.93	53.00	107
AGF08025*12H	B	12	6.0~13.2	1.54	8700	3.03	107.11	29.56	1.16	56.18	107
AGF08025*12U	B	12	6.0~13.2	2.39	9300	3.45	121.65	37.90	1.49	57.66	107
AGF08025*12V	B	12	6.0~13.2	2.54	10000	3.68	130.08	45.74	1.80	59.32	107
AGF08025*24L	B	24	12.0~26.4	0.25	7000	2.47	87.04	21.12	0.83	49.51	107
AGF08025*24M	B	24	12.0~26.4	0.30	7600	2.68	94.55	23.57	0.93	53.00	107
AGF08025*24H	B	24	12.0~26.4	0.40	8700	3.03	107.11	29.56	1.16	56.18	107
AGF08025*24U	B	24	12.0~26.4	0.45	9300	3.45	121.65	37.90	1.49	57.66	107
AGF08025*24V	B	24	12.0~26.4	0.60	10000	3.68	130.08	45.74	1.80	59.32	107

● Drawing & panel out-cuts/ 圖面及出入風口

● Characteristic Curves/ 特性曲線

