


60

AGF series

60X60X25mm



●General Specification / 一般規格

- Motor / DC brushless motor
- Material / Frame : plastic(94V-0)
- Impeller : plastic(94V-0)
- Bearing / Ball bearing;FMB
- Weight / 60g
- 馬達 / 直流單向無刷馬達
- 材質 / 框：塑膠(94V-0)
- 葉：塑膠(94V-0)
- 軸承 / 滾珠軸承;FMB
- 重量 / 60克

●Specification / 詳細規格 * 軸承/bearing B: 雙滾珠/ball bearing F:FMB S: 含油軸承/sleeve bearing

Model	Bearing	Voltage	Operating Vol.	Current	Speed	Max. Air Flow		Max. Static Pressure		Sound	Weight
機型	軸承	電壓	操作電壓	電流	轉速	最大風量		最大風壓		噪音	重量
P/N	B/S/F	V	V	A	RPM	m ³ /min	CFM	mm-H ₂ O	In-H ₂ O	dBA	g
AGF06025*12J	B	12	6.0~13.2	0.07	3100	0.49	17.4	3.20	0.13	30.73	60
AGF06025*12L	B	12	6.0~13.2	0.10	3600	0.56	19.84	4.26	0.17	31.38	60
AGF06025*12M	B	12	6.0~13.2	0.14	4250	0.68	24.05	5.97	0.24	34.63	60
AGF06025*12H	B	12	6.0~13.2	0.20	5000	0.78	27.68	7.17	0.28	37.43	60
AGF06025*12U	B	12	6.0~13.2	0.47	6800	1.10	38.89	13.84	0.54	42.42	60
AGF06025*12V	B	12	6.0~13.2	0.54	7500	1.21	42.68	16.76	0.66	45.11	60
AGF06025*12W	B	12	6.0~13.2	1.18	9800	1.60	56.49	28.52	1.12	50.70	60
AGF06025*24J	B	24	12.0~26.4	0.04	3100	0.49	17.4	3.20	0.13	30.73	60
AGF06025*24L	B	24	12.0~26.4	0.06	3600	0.56	19.84	4.26	0.17	31.38	60
AGF06025*24M	B	24	12.0~26.4	0.09	4250	0.68	24.05	5.97	0.24	34.63	60
AGF06025*24H	B	24	12.0~26.4	0.12	5000	0.78	27.68	7.17	0.28	37.43	60
AGF06025*24U	B	24	12.0~26.4	0.24	6800	1.10	38.89	13.84	0.54	42.42	60
AGF06025*48L	B	48	24.0~52.8	0.04	4250	0.68	24.05	5.97	0.24	34.63	60
AGF06025*48M	B	48	24.0~52.8	0.08	5000	0.78	27.68	7.17	0.28	37.43	60
AGF06025*48H	B	48	24.0~52.8	0.14	6800	1.10	38.89	13.84	0.54	42.42	60

● Drawing & panel out-cuts/ 圖面及出入風口

● Characteristic Curves/ 特性曲線

