

80

AGC series

80X80X25mm

●General Specification / 一般規格

- Motor / DC brushless motor
- Material / Frame : plastic(94V-0)
Impeller : plastic(94V-0)
- Bearing / Ball bearing;FMB
- Weight / 85g
- 馬達 / 直流單向無刷馬達
- 材質 / 框：塑膠(94V-0)
葉：塑膠(94V-0)
- 軸承 / 滾珠軸承;FMB
- 重量 / 85克



●Specification / 詳細規格 *軸承/bearing B: 雙滾珠/ball bearing F:FMB S: 含油軸承/sleeve bearing

Model	Bearing	Voltage	Operating Vol.	Current	Speed	Max. Air Flow		Max. Static Pressure		Sound	Weight
機型	軸承	電壓	操作電壓	電流	轉速	最大風量		最大風壓		噪音	重量
P/N	B/S/F	V	V	A	RPM	m ³ /min	CFM	mm-H ₂ O	In-H ₂ O	dBA	g
AGC08025*12L	B/F	12	6.0~13.2	0.11	2700	1.08	38.16	3.56	0.14	27.07	85
AGC08025*12M	B/F	12	6.0~13.2	0.17	3000	1.20	42.32	4.25	0.17	30.21	85
AGC08025*12H	B/F	12	6.0~13.2	0.21	3600	1.46	51.7	6.03	0.24	36.01	85
AGC08025*12U	B/F	12	6.0~13.2	0.44	4300	1.71	60.37	8.31	0.33	40.07	85
AGC08025*24J	B/F	24	12.0~26.4	0.06	2700	1.08	38.16	3.56	0.14	27.07	85
AGC08025*24L	B/F	24	12.0~26.4	0.08	3000	1.20	42.32	4.25	0.17	30.21	85
AGC08025*24M	B/F	24	12.0~26.4	0.11	3600	1.46	51.7	6.03	0.24	36.01	85
AGC08025*24H	B/F	24	12.0~26.4	0.17	4300	1.71	60.37	8.31	0.33	40.07	85
AGC08025*48J	B/F	48	24.0~52.8	0.04	2700	1.08	38.16	3.56	0.14	27.07	85
AGC08025*48L	B/F	48	24.0~52.8	0.06	3000	1.20	42.32	4.25	0.17	30.21	85
AGC08025*48M	B/F	48	24.0~52.8	0.08	3600	1.46	51.7	6.03	0.24	36.01	85
AGC08025*48H	B/F	48	24.0~52.8	0.13	4300	1.71	60.37	8.31	0.33	40.07	85

●Drawing & panel out-cuts/ 圖面及出入風口

●Characteristic Curves/ 特性曲線

