

80

AGK series

80X80X25mm

●General Specification / 一般規格

- Motor / DC brushless motor
- Material / Frame : plastic(94V-0)
Impeller : plastic(94V-0)
- Bearing / Ball bearing;FMB
- Weight / 85g
- 馬達 / 直流單向無刷馬達
- 材質 / 框：塑膠(94V-0)
葉：塑膠(94V-0)
- 軸承 / 滾珠軸承;FMB
- 重量 / 85克



●Specification / 詳細規格 * 軸承/bearing B: 雙滾珠/ball bearing F:FMB S: 含油軸承/sleeve bearing

Model	Bearing	Voltage	Operating Vol.	Current	Speed	Max. Air Flow		Max. Static Pressure		Sound	Weight
機型	軸承	電壓	操作電壓	電流	轉速	最大風量		最大風壓		噪音	重量
P/N	B/S/F	V	V	A	RPM	m ³ /min	CFM	mm-H ₂ O	In-H ₂ O	dBA	g
AGK08025*12J	B	12	6.0~13.2	0.13	3000	1.21	42.89	3.73	0.15	31.35	80
AGK08025*12L	B	12	6.0~13.2	0.18	3500	1.40	49.52	4.97	0.20	35.13	80
AGK08025*12M	B	12	6.0~13.2	0.26	4000	1.59	56.08	6.28	0.25	39.97	80
AGK08025*12H	B	12	6.0~13.2	0.35	4500	1.83	64.5	8.07	0.32	42.56	80
AGK08025*12U	B	12	6.0~13.2	0.45	5000	2.00	70.64	9.99	0.39	45.67	80
AGK08025*12V	B	12	6.0~13.2	0.60	5500	2.20	77.52	12.05	0.47	47.77	80
AGK08025*24J	B	24	12.0~26.4	0.06	3000	1.21	42.89	3.73	0.15	31.35	80
AGK08025*24L	B	24	12.0~26.4	0.08	3500	1.40	49.52	4.97	0.20	35.13	80
AGK08025*24M	B	24	12.0~26.4	0.14	4000	1.59	56.08	6.28	0.25	39.97	80
AGK08025*24H	B	24	12.0~26.4	0.20	4500	1.83	64.5	8.07	0.32	42.56	80
AGK08025*24U	B	24	12.0~26.4	0.21	5000	2.00	70.64	9.99	0.39	45.67	80
AGK08025*24V	B	24	12.0~26.4	0.26	5500	2.20	77.52	12.05	0.47	47.77	80

● Drawing & panel out-cuts/ 圖面及出入風口

● Characteristic Curves/ 特性曲線

