

150 AGR series

Φ172X51mm

●General Specification / 一般規格

- Motor / DC brushless motor
- Material / Frame : plastic(94V-0)
- Impeller : plastic(94V-0)
- Bearing / Ball bearing
- Weight / 590g
- 馬達 / 直流單向無刷馬達
- 材質 / 框：鋁合金壓鑄
- 葉：塑膠(94V-0)
- 軸承 / 滾珠軸承
- 重量 / 590克



●Specification / 詳細規格 * 軸承/bearing B: 雙滾珠/ball bearing F:FMB S: 含油軸承/sleeve bearing

Model	Bearing	Voltage	Operating Vol.	Current	Speed	Max. Air Flow		Max. Static Pressure		Sound	Weight
機型	軸承	電壓	操作電壓	電流	轉速	最大風量		最大風壓		噪音	重量
P/N	B/S/F	V	V	A	RPM	m ³ /min	CFM	mm-H ₂ O	In-H ₂ O	dBA	g
AGR15051*24J	B	24	12.0~26.4	0.80	3500	8.12	286.83	19.44	0.77	56.10	590
AGR15051*24L	B	24	12.0~26.4	1.25	4000	9.35	330.31	24.50	0.96	58.80	590
AGR15051*24M	B	24	12.0~26.4	1.55	4400	10.17	359.15	27.94	1.10	61.50	590
AGR15051*24H	B	24	12.0~26.4	1.85	4800	11.14	393.28	32.08	1.26	64.20	590
AGR15051*24U	B	24	12.0~26.4	2.25	5200	11.96	422.32	36.30	1.43	67.80	590
AGR15051*48J	B	48	24.0~52.8	0.50	3500	8.12	286.83	19.44	0.77	56.10	590
AGR15051*48L	B	48	24.0~52.8	0.65	4000	9.35	330.31	24.50	0.96	58.80	590
AGR15051*48M	B	48	24.0~52.8	0.80	4400	10.17	359.15	27.94	1.10	61.50	590
AGR15051*48H	B	48	24.0~52.8	0.95	4800	11.14	393.28	32.08	1.26	64.20	590
AGR15051*48U	B	48	24.0~52.8	1.30	5200	11.96	422.32	36.30	1.43	67.80	590

●Drawing & panel out-cuts/ 圖面及出入風口

●Characteristic Curves/ 特性曲線

